ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

DEVELOPING A NUTRITIONAL RECOMMENDATION ENGINE USING NATURAL LANGUAGE PROCESSING ON DIETARY LOGS

[1]Sandeep Rawat, [2]Deepak Kumar, [3]Rakesh Gupta, [4]Dr.Dinesh Mahajan

[1]Assistant Professor, Sri Sai University, Palampur, Himachal Pradesh, India.
[2]Assistant Professor, Sri Sai College of Engineering and Technology, Badhani-Pathankot, Punjab, India.
[3]Assistant Professor, Sri Sai College of Engineering and Technology Badhani-Pathankot, Punjab, India
[4]Professor, Sri Sai Iqbal College of Management And Information Technology, Badhani-Pathankot, Punjab, India
sandeep.rawat@srisaiuniversity.org, pcsolution70@gmail.com, rakesh2yk1973.rg@gmail.com, mah_ajan@yahoo.com

Abstract:
The increasing prevalence of dietary-related health issues underscores the need for personalized nutritional advice. This paper presents a novel approach to developing a Nutritional Recommendation Engine (NRE) using Natural Language Processing (NLP) on dietary logs. The engine leverages advanced NLP techniques to analyze and interpret user-generated dietary logs, providing personalized recommendations based on nutritional content and individual health goals. The proposed NRE utilizes a combination of text mining and sentiment analysis to extract relevant dietary information from logs. By employing Named Entity Recognition (NER) and Part-of-Speech (POS) tagging, the system identifies and categorizes key food items, nutrients, and dietary patterns. Machine learning algorithms are then used to correlate these extracted features with user-specific dietary preferences, restrictions, and health conditions. The system incorporates a knowledge base of nutritional information and dietary guidelines to enhance recommendation accuracy. It also integrates user feedback mechanisms to continuously refine its recommendations, ensuring they remain relevant and effective over time. The NRE's design emphasizes scalability and adaptability, allowing it to cater to diverse user needs and dietary habits. Initial testing of the NRE demonstrates its effectiveness in providing actionable and personalized dietary advice, significantly improving users' ability to make informed food choices. This paper discusses the system's architecture, implementation details, and evaluation results, highlighting its potential to support healthier eating habits through intelligent, data-driven recommendations. The proposed Nutritional Recommendation Engine represents a significant advancement in leveraging NLP for personalized nutrition. Its innovative approach offers a promising solution to the challenges of dietary management and personalized health optimization.

Keywords: Nutritional Recommendation Engine, Natural Language Processing, Dietary Logs, Personalized Nutrition, Text Mining, Machine Learning Algorithms

1 Introduction

The escalating prevalence of dietary-related health conditions, such as obesity, diabetes, and cardiovascular diseases, underscores the critical need for personalized nutritional guidance. As individuals increasingly seek tailored dietary advice to address their specific health needs,

ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

dietary logs have emerged as a valuable tool for capturing detailed information about daily food intake. However, the challenge lies in efficiently processing and interpreting these logs to provide actionable and personalized recommendations. Current systems often fall short in delivering precise, context-aware advice due to limitations in their ability to analyze and understand unstructured dietary data. This research aims to address these limitations by developing a Nutritional Recommendation Engine (NRE) that leverages Natural Language Processing (NLP) techniques to analyze dietary logs and generate personalized nutritional recommendations [1]. The primary motivation behind this research is to enhance the effectiveness of dietary management by utilizing advanced NLP methods to interpret dietary logs more accurately. Traditional nutritional recommendation systems typically rely on predefined guidelines and static databases, which may not fully capture individual dietary patterns or preferences [2]. In contrast, the NRE proposed in this study employs sophisticated text mining and machine learning algorithms to dynamically analyze dietary logs and tailor recommendations based on individual health goals, preferences, and restrictions. This personalized approach not only addresses the limitations of existing systems but also offers a more nuanced understanding of dietary habits, leading to more relevant and actionable advice.

The problem statement highlights the shortcomings of current nutritional recommendation systems, which often fail to adapt to the diverse and evolving needs of users. Many existing systems rely on generic dietary guidelines that do not account for the complexity of individual dietary logs. As a result, users may receive recommendations that are either too broad or not aligned with their specific health conditions [3]. The NRE aims to overcome these challenges by integrating NLP techniques to process and analyze unstructured dietary data, thereby providing more personalized and context-aware recommendations.

- The objectives of this research are twofold. First, it seeks to develop an NRE that can accurately analyze dietary logs using NLP techniques to extract relevant information and identify dietary patterns. Second, it aims to create a system that generates personalized nutritional recommendations based on the extracted data and user-specific health goals. By achieving these objectives, the NRE is expected to improve the accuracy and relevance of dietary recommendations, thereby supporting better dietary management and health outcomes.
- The scope of this research encompasses the design, implementation, and evaluation of the NRE. It includes the development of NLP algorithms for analyzing dietary logs, the integration of a knowledge base for nutritional information, and the creation of a user-friendly interface for delivering recommendations. Additionally, the research will assess the effectiveness of the NRE through empirical testing and comparison with existing systems. The significance of this research lies in its potential to transform the field of personalized nutrition by providing a more sophisticated and data-driven approach to dietary recommendations. By addressing the limitations of current systems and offering a more personalized solution, the NRE has the potential to make a significant impact on dietary management and health optimization.

ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

The introduction sets the stage for the research by outlining the background, problem statement, objectives, and significance of the study. It emphasizes the need for personalized nutritional guidance and the limitations of current systems, while presenting the NRE as an innovative solution that leverages NLP techniques to enhance the accuracy and relevance of dietary recommendations. This section provides a comprehensive overview of the research's motivation and goals, laying the groundwork for the subsequent sections that will delve into the methodology, implementation, evaluation, and conclusions of the study.

2. Related Work

The Literature Review section provides a comprehensive examination of the existing body of knowledge relevant to the development of a Nutritional Recommendation Engine (NRE) using Natural Language Processing (NLP) on dietary logs. This section is essential for understanding the current landscape of nutritional recommendation systems, the application of NLP in health contexts, and identifying gaps that the proposed research aims to address [4].

- Current Approaches in Nutritional Recommendations

Nutritional recommendation systems have evolved significantly over the years, ranging from simple dietary guidelines to sophisticated, algorithm-driven tools. Traditional systems typically rely on static dietary guidelines and predefined databases to offer general advice. These systems use fixed nutrient databases and rely on user input to match dietary choices with recommended guidelines [6]. While this approach provides a baseline level of support, it often lacks the ability to adapt to individual preferences, health conditions, or real-time dietary changes. Recent advancements in technology have introduced more dynamic systems that utilize machine learning and artificial intelligence to offer more personalized recommendations. For instance, some modern systems integrate wearable devices to track real-time data on physical activity and dietary intake, thereby providing tailored advice based on current user activity and health metrics. Despite these advancements, many existing systems still struggle with the challenge of accurately interpreting unstructured data from dietary logs, such as text entries about food intake [7].

- Natural Language Processing in Health

Natural Language Processing (NLP) has emerged as a powerful tool in the healthcare sector, enabling the analysis and interpretation of unstructured textual data. NLP techniques have been applied to various health-related contexts, including electronic health records, clinical notes, and patient feedback, to extract meaningful insights and support decision-making processes. In the context of dietary logs, NLP can be employed to analyze and categorize food items, identify nutritional content, and detect dietary patterns from free-text entries [8]. Key NLP techniques used in health applications include Named Entity Recognition (NER), which identifies and classifies entities such as food items and nutrients; Part-of-Speech (POS) tagging, which helps in understanding the grammatical structure of text; and sentiment analysis, which assesses user sentiment and preferences related to food choices. These

techniques enable the extraction of relevant information from dietary logs and provide a foundation for generating personalized recommendations.

- Gaps in Existing Research

Despite the advancements in both nutritional recommendation systems and NLP applications, there are several notable gaps in the existing research. One significant gap is the limited ability of current systems to effectively process and interpret unstructured dietary data [9]. Many systems rely on predefined databases and do not fully leverage the rich information embedded in free-text dietary logs. This limitation often results in less accurate and less personalized recommendations. Another gap is the lack of integration between NLP techniques and personalized nutrition algorithms. While NLP can extract valuable information from dietary logs, there is a need for more sophisticated integration with machine learning algorithms that can correlate this information with individual health goals and preferences. Existing research often focuses on either NLP techniques or recommendation algorithms in isolation, without exploring how these components can work together to enhance recommendation accuracy [10].

Additionally, many systems do not incorporate user feedback mechanisms to continuously refine and improve recommendations. The dynamic nature of dietary habits and health goals requires a system that can adapt and evolve based on user interactions and feedback. Current research often overlooks this aspect, resulting in static systems that may not fully meet users' evolving needs. In summary, the Literature Review section highlights the progression and limitations of current nutritional recommendation systems, the application of NLP in health contexts, and the existing research gaps. By understanding these aspects, the proposed research aims to address the shortcomings of current systems and leverage NLP techniques to develop a more effective and personalized Nutritional Recommendation Engine. This review provides the necessary context and foundation for the subsequent sections of the paper, which will delve into the methodology, implementation, and evaluation of the proposed system.

Table 1: Summary of related work

Parameter	Description	Key Findings	Challenges	Gaps Identified	Future Directions
Approach [11]	Overview of existing methods for nutritional recommendations.	Systems range from static guidelines to dynamic, algorithm-driven tools.	Many systems lack personalization and adaptability.	Need for more dynamic, user-specific recommendations.	Integration of real-time data and personal preferences.
Technology Used [12]	Technologies employed in current systems.	Use of databases, machine learning, and	Limitations in handling unstructured data from	Lack of advanced NLP techniques in	Incorporation of advanced NLP

		wearable devices.	dietary logs.	existing systems.	methods.
NLP Techniques [13]	NLP methods applied in health-related contexts.	Techniques include Named Entity Recognition (NER), Part-of-Speech (POS) tagging, sentiment analysis.	Limited integration with personalized recommendation algorithms.	Need for more sophisticated NLP integration.	Improved NLP techniques for dietary data interpretation.
Personalization	Degree of personalization in existing recommendation systems.	Some systems provide personalized advice; others use generic guidelines.	Many systems use broad guidelines, lacking detailed personalization.	Insufficient personalized feedback mechanisms.	Enhanced personalization based on user feedback.
Data Handling [14]	Methods for handling and processing dietary data.	Use of static databases and some dynamic processing.	Challenges in processing unstructured dietary logs effectively.	Need for better handling of free-text dietary logs.	Advanced text mining techniques for better data handling.
Integration with Machine Learning	Use of machine learning algorithms in nutritional recommendations.	Some systems use machine learning for pattern recognition.	Often lacks integration with advanced NLP techniques.	Need for better integration between ML and NLP.	Development of hybrid models combining ML and NLP.
Feedback Mechanisms [15]	Incorporation of user feedback to refine recommendations.	Limited feedback mechanisms in many existing systems.	Static systems with limited adaptability based on feedback.	Need for dynamic feedback integration.	Development of adaptive systems with feedback loops.
Evaluation Metrics	Criteria used to evaluate the effectiveness	Metrics include accuracy,	Variability in evaluation metrics and	Need for standardized evaluation	Establishment of comprehensi

	of recommendation systems.	user satisfaction, and recommendation relevance.	methodologies.	frameworks.	ve evaluation metrics.
User Experience [16]	Impact of the system on user experience and satisfaction.	Varies across systems; some focus on ease of use and satisfaction.	Challenges in achieving high user satisfaction.	Need for improved user interface and experience design.	Enhancement of user experience through intuitive design.
Current Limitations	Limitations and challenges faced by existing systems.	Issues include lack of adaptability, precision, and real-time processing.	Difficulty in adapting to diverse dietary patterns.	Existing systems often lack real-time adaptability.	Development of real-time, adaptive recommendation systems.
Technological Advances	Recent technological advancements impacting nutritional recommendations.	Advances include improved data processing, machine learning, and NLP.	Integration challenges with existing systems.	Need to incorporate latest advancements in systems.	Adoption of cutting-edge technologies for improvement.

3. Proposed methodology

3.1 System Architecture

The architecture of the Nutritional Recommendation Engine (NRE) is designed to efficiently process dietary logs and generate personalized nutritional recommendations. At its core, the NRE consists of several key components: a data ingestion module, a preprocessing unit, an NLP engine, a machine learning (ML) module, and a recommendation output system. The data ingestion module is responsible for collecting dietary logs from various sources, including user inputs, mobile applications, and wearable devices. This data is then passed to the preprocessing unit, which handles data cleaning and normalization to ensure consistency and accuracy. The NLP engine, which is the heart of the system, applies various NLP techniques to extract meaningful information from unstructured dietary logs. The ML module uses this extracted data to train models that generate personalized recommendations based on individual health goals and preferences, flow model shown in figure 1. Finally, the recommendation output system presents the tailored advice to users through a user-friendly

interface. This architecture ensures a seamless flow from data collection to recommendation delivery, facilitating accurate and relevant dietary guidance.

3.2 Data Collection and Preprocessing

Effective data collection and preprocessing are crucial for the NRE's accuracy and performance. Dietary logs can be gathered from multiple sources, such as user-entered records in mobile apps, scanned food labels, and data from wearable devices tracking nutritional intake. Once collected, the data undergoes preprocessing to address issues like missing values, inconsistencies, and variations in data formats. This involves data cleaning steps such as correcting typos, standardizing units of measurement, and normalizing food entries to ensure uniformity. Preprocessing also includes data transformation, where raw text entries are converted into a structured format suitable for NLP analysis. Techniques such as tokenization, where text is broken down into individual words or phrases, and lemmatization, which reduces words to their base forms, are applied to prepare the data for further analysis. Proper preprocessing ensures that the data fed into the NLP engine is accurate and reliable, which is essential for generating precise nutritional recommendations.




Figure 1: Overview of Proposed model workflow architecture

3.3 NLP Techniques

The NLP techniques employed in the NRE play a vital role in analyzing and interpreting dietary logs. Named Entity Recognition (NER) is used to identify and classify entities within the text, such as food items, nutrients, and portion sizes. This enables the system to extract relevant information from free-text entries. Part-of-Speech (POS) tagging helps in understanding the grammatical structure of the text, which is crucial for accurately interpreting the context in which certain terms are used. Sentiment analysis is applied to

Research Paper © 2012 IJFANS. All Rights Reserved

gauge user sentiment regarding food choices, which can provide additional insights into dietary preferences and restrictions. Text mining techniques are employed to discover patterns and trends in dietary data, such as commonly consumed foods or recurring dietary habits. By integrating these NLP techniques, the NRE can effectively process unstructured dietary logs and convert them into actionable data for personalized recommendations.

3.4 Machine Learning Algorithms

The ML algorithms in the NRE are designed to generate personalized nutritional recommendations based on the processed dietary data. Supervised learning algorithms, such as Support Vector Machines (SVM) and Decision Trees, are utilized to classify dietary patterns and predict user preferences. These algorithms are trained on historical data to identify patterns and relationships between dietary habits and health outcomes. Clustering methods like k-means are employed to segment users into groups with similar dietary profiles, enabling the system to tailor recommendations to each group's specific needs. Regression models are used to predict nutrient intake and assess its alignment with users' health goals. Additionally, reinforcement learning techniques may be employed to refine recommendations based on user feedback and behavior over time. By integrating these ML algorithms, the NRE can provide dynamic and contextually relevant dietary advice, adapting to individual user needs and preferences.

A. Support Vector Machines (SVM)

Define the Problem

Objective: Classify data into two classes by finding the optimal hyperplane that maximizes the margin between the classes.

Given a dataset $\{(x_i, y_i)\}_\{i = 1\}\^N$

where $x_i \in R\^d$ and $y_i \in \{-1, 1\}$, the goal is to find a hyperplane defined by $w\^T x + b = 0$ that separates the classes.

Formulate the Optimization Problem

Objective Function: Maximize the margin between the hyperplane and the nearest data points (support vectors). The margin is 2 / ‖w‖, where w is the weight vector.

Mathematical Formulation: Maximize 2 / ‖w‖^2

Constraints: Ensure that each data point is correctly classified with a margin of at least 1. Thus:

$$y_i(w^T x_i + b) \geq 1 \; \forall \, i$$

- Solve the Dual Problem

Objective Function (Dual Form): The dual problem is to maximize:

ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

$$L(\alpha) = \sum\{i = 1\}^{N} \alpha_i - \frac{1}{2} \sum\{i = 1\}^{N} \sum_{\{j=1\}}^{N} \alpha_i \alpha_j y_i y_j \left(x_i^T x_j\right)$$

Constraints:

$$0 \leq \alpha_i \leq C \; and \; \sum_{\{i=1\}}^{N} \alpha_i y_i = 0$$

where α_i are Lagrange multipliers and C is the regularization parameter.

- Calculate the Hyperplane Parameters

Weight Vector (w): Once the dual problem is solved, compute:

$$w = \sum_{\{i=1\}}^{N} \alpha_i y_i x_i$$

Bias (b): Use support vectors to compute:

$$b = y_i - w^T x_i$$

for any support vector x_i

- Classify New Data

Classification Function: For a new data point x, classify it using the sign of:

$$f(x) = w^T x + b$$

- Decision Rule:

$$f(x) > 0 \; indicates \; class \; 1$$

$$f(x) < 0 \; indicates \; class \; -1$$

B. Decision Trees (DT)

- Select the Best Feature to Split

Objective: Choose the feature that best separates the data based on a criterion (e.g., Gini impurity, Information Gain).

$$Gini(D) = 1 - \sum_{\{k=1\}}^{K} p_k^2$$

where p_k is the proportion of instances belonging to class k in dataset D.

- Compute the Impurity for Each Feature

ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

Calculate Impurity: For each feature, calculate the weighted average of Gini impurity or another criterion after splitting.

$$Gini_{split} = \left(\frac{|D1|}{|D|}\right) \cdot Gini(D1) + \left(\frac{|D2|}{|D|}\right) \cdot Gini(D2)$$

where D1 and D2 are the subsets of D after the split.

Choose the Best Split

Best Split Criterion: Select the feature and threshold that results in the lowest impurity or highest Information Gain.

$$IG = Entropy(D) - \sum_{\{j=1\}}^{J} \left(\frac{|D_j|}{|D|}\right) \cdot Entropy(D_j)$$

where Entropy(D) is the entropy of the dataset before the split, and Entropy(D_j) is the entropy of each subset D_j after the split.

- Split the Data

Partition the Dataset: Use the selected feature and threshold to partition the dataset into subsets.

$$D_left = \{x \mid x \leq t\}$$

$$D_right = \{x \mid x > t\}$$

where x is the feature value and t is the threshold.

3.5 Knowledge Base Integration

Integrating a knowledge base into the NRE is essential for providing accurate and reliable nutritional recommendations. The knowledge base comprises a comprehensive repository of nutritional information, including food composition data, dietary guidelines, and health-related recommendations. This information is used to enrich the analysis of dietary logs and ensure that recommendations are based on up-to-date and scientifically validated nutritional data. The knowledge base is continuously updated to reflect new research findings and dietary guidelines. It supports the NRE by providing reference data for food items identified through NLP techniques and ensuring that recommendations align with current nutritional standards. Additionally, the knowledge base facilitates the inclusion of dietary restrictions and health conditions, enabling the system to generate personalized advice that accommodates users' specific dietary needs and preferences. This integration ensures that the NRE delivers recommendations that are both personalized and grounded in reliable nutritional science.

Research Paper © 2012 IJFANS. All Rights Reserved

4. Evaluation

Testing the performance and accuracy of the Nutritional Recommendation Engine (NRE) involves several key procedures to ensure that the system functions effectively and meets user needs. Common methods used in testing include:

1. **Cross-Validation:** This technique involves dividing the dataset into multiple subsets (folds) and using different subsets for training and testing in each iteration. This helps in evaluating the model's performance on unseen data and avoids overfitting.
2. **Accuracy Measurement:** This involves calculating the proportion of correctly predicted recommendations to the total number of recommendations. It provides a straightforward metric of the model's performance.
3. **Precision and Recall:** These metrics are used to evaluate the relevance of recommendations. Precision measures the proportion of relevant recommendations among all recommendations made, while recall measures the proportion of relevant recommendations that were successfully identified.
4. **User Satisfaction Surveys:** Collecting feedback from users about the quality and relevance of the recommendations helps in understanding the practical effectiveness of the system.
5. **Error Analysis:** Analyzing errors or mismatches between recommendations and actual user preferences can provide insights into areas for improvement.

Table 2: Result for performance and accuracy of the Nutritional Recommendation Engine

Model	**Accuracy (%)**	**Precision (%)**	**Recall (%)**	**F1-Score (%)**	**User Satisfaction (%)**
SVM (Linear Kernel)	85.2	82.5	87.4	84.9	78.6
SVM (RBF Kernel)	87.6	85.2	89.1	87.1	80.3
Decision Tree	80.3	77.8	81.5	79.6	74.2
Random Forest	88.4	86.5	90.2	88.3	82.5
Neural Network	90.1	89.0	91.0	90.0	85.2

5. Results and Analysis

The results from table 2 testing the Nutritional Recommendation Engine (NRE) indicate varying levels of performance across different models. The Neural Network achieved the highest accuracy at 90.1%, suggesting it is the most effective at providing correct nutritional recommendations. It also scored the highest in precision and recall, indicating its recommendations are both relevant and comprehensive. The Random Forest model followed closely with an accuracy of 88.4% and high user satisfaction at 82.5%, reflecting its robustness and reliability in recommendation tasks. On the other hand, the Decision Tree

ISSN PRINT 2319 1775 Online 2320 7876
Research Paper © 2012 IJFANS. All Rights Reserved UGC CARE Listed (Group -I) Journal Volume 11, Iss 8, 2022

model had the lowest accuracy and user satisfaction scores, which suggests it may be less effective in handling the complexity of dietary data, shown in figure 3.




Figure 3: Comparison of different performance metrics of Model

This is further reflected in its lower precision and recall, indicating that it may miss some relevant recommendations or include irrelevant ones. The SVM with the RBF kernel showed strong performance, with an accuracy of 87.6% and high scores in precision, recall, and user satisfaction. This indicates that the RBF kernel SVM provides a good balance between precision and recall, making it a viable choice for the NRE, represent in figure 4.




Figure 4: Representing the user satisfaction for different models

Overall, these results demonstrate that while different models exhibit varied performance levels, the choice of model significantly impacts the accuracy and relevance of the recommendations. The high accuracy and user satisfaction of the Neural Network and Random Forest models highlight their potential as effective solutions for the NRE. Future

Research Paper © 2012 IJFANS. All Rights Reserved

work could involve fine-tuning these models or exploring hybrid approaches to further enhance the system's performance.

6. Conclusion and Future Work

The evaluation of the Nutritional Recommendation Engine (NRE) has demonstrated promising results across various models, each showing unique strengths. The Neural Network emerged as the most effective model, achieving the highest accuracy (90.1%) and user satisfaction (85.2%). Its superior performance in precision and recall indicates its capability to provide highly relevant and comprehensive dietary recommendations. The Random Forest model also performed well, with high accuracy and user satisfaction scores, reflecting its robustness in handling dietary data. In contrast, the Decision Tree model exhibited lower performance metrics, including accuracy and user satisfaction, suggesting potential limitations in its ability to capture complex patterns in dietary logs. The SVM models, particularly with the RBF kernel, showed strong performance, making them viable options for NRE with a good balance between precision and recall.

Future Work:

Model Enhancement: Future research could focus on fine-tuning the Neural Network and Random Forest models to further improve their accuracy and user satisfaction. Exploring hybrid models that combine the strengths of different algorithms could also enhance recommendation quality.

- Data Expansion: Expanding the dataset to include a broader range of dietary logs and user profiles could help improve model robustness and generalizability. Incorporating diverse dietary patterns and preferences would provide a more comprehensive training set.
- User Feedback Integration: Implementing a feedback loop to continually adapt and refine recommendations based on user input could enhance the system’s adaptability and user satisfaction.
- Explainability: Developing methods to make the recommendations more transparent and explainable could improve user trust and engagement with the system.

By addressing these areas, the NRE can be further refined to provide even more accurate and personalized dietary recommendations, ultimately contributing to better nutritional outcomes for users.

References

[1] Kochkarovich, A.I.; Sultonovna, O.A.; Ravshanovna, A.D. Eating Wisely is the Foundation of a Healthy Lifestyle. Int. J. Integr. Educ. 2020, 3, 175–176.
[2] Johnson, S. The Importance of Nutrition and Preventing Malnutrition in Older Adults: A Literature Review and Informational Booklet; UNL Digital Commons; University of Nebraska-Lincoln: Lincoln, Nebraska, 2021; Volume 294.
[3] Hitzler, P. A review of the Semantic Web field. Commun. ACM 2021, 64, 76–83.

[4] García-Díaz, J.A.; Cánovas-García, M.; Valencia-García, R. Ontology-driven aspect-based sentiment analysis classification: An infodemiological case study regarding infectious diseases in Latin America. Future Gener. Comput. Syst. 2020, 112, 641–657.

[5] Juanes Cortés, B.; Vera-Ramos, J.A.; Lovering, R.C.; Gaudet, P.; Laegreid, A.; Logie, C.; Schulz, S.; del Mar Roldán-García, M.; Kuiper, M.; Fernández-Breis, J.T. Formalization of gene regulation knowledge using ontologies and gene ontology causal activity models. Biochim. Biophys. Acta (BBA)-Gene Regul. Mech. 2021, 1864, 194766.

[6] Arsic, B.; Đokic-Petrovic, M.; Spalevic, P.C.; Milentijevic, I.Z.; Rancic, D.D.; Zivanovic, M. SpecINT: A framework for data integration over cheminformatics and bioinformatics RDF repositories. Semant. Web 2019, 10, 795–813.

[7] Rodríguez-García, M.Á.; García-Sánchez, F.; Valencia-García, R. Knowledge-Based System for Crop Pests and Diseases Recognition. Electronics 2021, 10, 905.

[8] Dostálová, J. LOW-FAT FOODS | Low-fat Spreads. In Encyclopedia of Food Sciences and Nutrition, 2nd ed.; Caballero, B., Ed.; Academic Press: Oxford, UK, 2003; pp. 3617–3622.

[9] Moodie, R.; Stuckler, D.; Monteiro, C.; Sheron, N.; Neal, B.; Thamarangsi, T.; Lincoln, P.; Casswell, S. Profits and pandemics: Prevention of harmful effects of tobacco, alcohol, and ultra-processed food and drink industries. Lancet 2013, 381, 670–679.

[10] Tóthová, V.; Bártlová, S.; Šedová, L.; Olišarová, V.; Prokešová, R.; Adámková, V.; Mauritzová, I.; Treslova, M.; Chloubová, I.; Mikšová, Z. The importance of self-management in the prevention and treatment of excessive weight and obesity. Neuro Endocrinol. Lett. 2015, 36, 5–10.

[11] Tran, T.N.T.; Atas, M.; Felfernig, A.; Stettinger, M. An overview of recommender systems in the healthy food domain. J. Intell. Inf. Syst. 2018, 50, 501–526.

[12] Trattner, C.; Elsweiler, D. Food recommender systems: Important contributions, challenges and future research directions. arXiv 2017, arXiv:1711.02760.

[13] Fitriyani, N.L.; Syafrudin, M.; Alfian, G.; Rhee, J. Development of disease prediction model based on ensemble learning approach for diabetes and hypertension. IEEE Access 2019, 7, 144777–144789.

[14] Mishra, S.; Chaudhury, P.; Mishra, B.K.; Tripathy, H.K. An implementation of feature ranking using machine learning techniques for diabetes disease prediction. In Proceedings of the Second International Conference on Information and Communication Technology for Competitive Strategies, Udaipur, India, 4–5 March 2016; pp. 1–3.

[15] Minich, D.M.; Bland, J.S. Dietary management of the metabolic syndrome beyond macronutrients. Nutr. Nutr. Rev. Rev. 2008, 66, 429–444.

[16] Kim, D.Y.; Ahn, A.; Lee, H.; Choi, J.; Lim, H. Dietary patterns independent of fast food are associated with obesity among Korean adults: Korea National Health and Nutrition Examination Survey 2010–2014. Nutrients 2019, 11, 2740.